



WWW.ZEUSINC.COM

# PTFE Spiral-Cut Cable Wrap

SPECIALTY PRODUCTS



## Dimensions (inches)

Ordered by Outside Diameter A	Cut From PTFE, FEP, PFA, ETFE Industrial Tubing Size I.D. B	Wall C	Bundle Diameter Maximum D	Pitch of Helical Cut E
1/8 (.125)	1/16	0.030	1/2	1/4 (.218)
3/16 (.188)	1/8	0.030	1	1/32 (.312)
1/4 (.250)	3/16	0.030	2	3/8 (.375)
5/16 (.313)	1/4	0.030	2-1/2	3/8 (.375)
3/8 (.375)	5/16	0.030	3	7/16 (.437)
1/2 (.500)	7/16	0.030	4	9/16 (.562)
5/8 (.625)	9/16	0.030	5	5/8 (.625)
3/4 (.750)	11/16	0.032	6	7/8 (.875)
1 (1.000)	15/16	0.040	8	1 (1.000)

## Metric Dimensions (mm)

Ordered by Outside Diameter A	Cut From PTFE, FEP, PFA, ETFE Industrial Tubing Size I.D. B	Wall C	Bundle Diameter Maximum D	Pitch of Helical Cut E
3.18	1.59	0.76	12.70	6.35
4.76	3.18	0.76	25.40	6.35
6.35	4.76	0.76	50.80	9.53
7.94	6.35	0.76	63.50	9.53
9.53	7.94	0.76	76.20	11.11
12.70	11.11	0.76	101.60	14.29
15.88	14.29	0.76	127.00	15.88
19.05	17.46	1.02	152.40	22.23
25.40	23.81	1.02	203.20	25.40

Supplied in natural unless otherwise specified.  
Custom Pantone colors or ZEUS standard colors available on request.

OD tolerance +/- .005", Wall Tolerance +/- .005",  
Pitch Tolerance +/- .030".

Material and dimensions comply with ASTM 3295 Group 4. Annual testing data provided. Lot to lot testing available upon request.

ZEUS SPIRAL-CUT CABLE WRAPS are expandable abrasion-resistant wraps for harnessing and insulating wires, cable, and bundles. ZEUS SPIRAL CUT CABLE WRAP is extruded to close tolerances and then precision cut.

Use chart and letters shown when ordering

"A" = O.D. of PTFE Tubing

"B" = I.D.

"C" = Wall Thickness

"D" = Maximum Bundle Diameter

"E" = Pitch

